


SENSAR 1-Piece Hydrophobic Acrylic IOL



DESCRIPTION	
OPTIC CHARACTERISTICS	
Powers:	+6.0 D to +30.0 D in 0.5 diopter increments
Diameter:	6.0 mm
Material:	UV-blocking hydrophobic acrylic
Refractive Index:	1.47 at 35°C
Edge Design:	ProTEC frosted, continuous 360° posterior square edge
ULTRASOUND BIOMETRY*	
A-constant:	118.4
Theoretical AC Depth:	5.2 mm
Surgeon Factor: ¹	1.45 mm
HAPTIC CHARACTERISTICS	
Overall Diameter:	13.0 mm
Style:	C
Material:	UV-blocking hydrophobic acrylic
Design:	Haptics offset from optic
RECOMMENDED INSERTION INSTRUMENTS	MODEL
UNFOLDER Platinum 1 Series Handpiece	DK7796
UNFOLDER Platinum 1 Series Cartridge	1MTEC30
One Series Ultra Implantation System (Syringe-style Inserter)	DK7786
One Series Ultra Cartridge	1VIPR30

*Value theoretically derived for a typical 20.0 D lens. Johnson & Johnson Vision recommends that surgeons personalize their A-constant based on their surgical techniques and equipment, experience with the lens model, and postoperative results.

To learn more and to view important safety information, please contact your Johnson & Johnson Vision Sales Representative.

1. Holladay JT. International Intraocular Lens & Implant Registry 2003. *J Cataract Refract Surg.* 2003; 29:176-197. REF2016CT0151.

SENSAR® 1-piece lenses are indicated for the visual correction of aphakia in adult patients in whom a cataractous lens has been removed by extracapsular cataract extraction. These devices are intended to be placed in the capsular bag. For a complete listing of precautions, warnings, and adverse events, refer to the package insert.

One Series, SENSAR, ProTEC and UNFOLDER are trademarks of Johnson & Johnson Surgical Vision, Inc. ©Johnson & Johnson Surgical Vision, Inc. 2018

For healthcare professionals only.

PP2018OTH4091